

ODV-3-220043-1F12-MN

Optidrive Eco VFD Datasheet

0.75 kW (1 HP), 4.3 A, 200-240 V, 1-3PH
IP20 Variable Frequency Drive with EMC
Filter and TFT Display



Input Ratings

| | |
|-----------------------------|-----------|
| Supply Voltage | 200-240 V |
| Input Phases | 1 |
| Supply Current Continuous | 8.5 A |
| Supply Fuse or MCB (Type B) | 10 A |

Output Ratings

| | |
|---------------------|--------------------|
| Motor Output Rating | 0.75 kW (1 HP) |
| Output Voltage | 0 – Supply Voltage |
| Output Current | 4.3 A |

Cable Information

| | |
|------------------------|--------------------------------|
| Max Supply Cable Size | 8 mm ² (0.01 sq in) |
| Max Motor Cable Size | 8 mm ² (0.01 sq in) |
| Max Motor Cable Length | 100 m (328 ft) |

Factory Build Options

| | |
|------------------|---------------------|
| EMC Filter | Internal EMC |
| Brake Transistor | No Brake Transistor |
| Enclosure | IP20 |
| Display | TFT Display |
| PCB Coating | Standard |

Dimensions

| | |
|---------|-------------------|
| Size | 2 |
| Height | 221 mm (8.7 in) |
| Width | 110 mm (4.33 in) |
| Depth | 185 mm (7.28 in) |
| Weight | 1.8 kg (3.97 lbs) |
| Fixings | 4 x M4 |

Packaged Dimensions

| | |
|--------|-------------------|
| Height | 265 mm (10.43 in) |
| Width | 145 mm (5.71 in) |
| Depth | 230 mm (9.06 in) |
| Weight | 1.9 kg (4.19 lbs) |



 **Buy this drive or get more information**
Find your local sales partner on
invertekdrives.com



How we measure our drives and packaging



Drive Dimensions



Packaging Dimensions



Buy this drive or get more information

Find your local sales partner on
invertekdrives.com

