



| | |
|-------------------|---------------------------------|
| Specification | IEC 60034-1 |
| Manufacturer | AmTecs |
| Motor type | AMA3-IE3 160L4 |
| Rated power | 15 kW S1 Duty |
| Speed | 1465 rpm |
| Voltage | 400V / 690V |
| Frequency | 50 Hz |
| Connection | Delta / Star |
| Full load current | 28.6 A / 16.51 A |
| No-load current | |
| Enclosure | IP55 |
| Insulation class | F (temp. rise B) |
| Max. ambient temp | 40 °C |
| Max. altitude | 1000 mtr above sea level |
| Comment | |
| Cable entry | M32 x 1.5 |
| Construction | Aluminium |
| Weight | 117 Kg |
| Type number | |
| Warranty | |

| | |
|------------------------------------|-----------------|
| Efficiency class | IE3 |
| Load data | 100% |
| Efficiency | 92.1 % |
| Power factor | 0.82 |
| Sound pressure level (1m) | 63 dB(A) |
| Resistance R20 (open) | |
| Resistance R20 (Delta) | |
| Full load torque | 97.8 Nm |
| Starting / Full load torque | 1.8 |
| Pull up / Full load torque | |
| Pull out / Full load torque | 2.4 |
| Starting / Full load current (DOL) | 6.8 |
| Starting / Full load current (Y/D) | |
| Rotor Inertia | |
| Bearing DE | 6309 |
| Bearing NDE | 6209 |

| | |
|--|--------------------|
| AmTecs Ltd | |
| Charnham Park, Hungerford Berkshire, RG17 0YT | |
| Tel: +44 (0) 1488 686970 | sales@amtecs.co.uk |
| Fax: +44 (0) 1488 686968 | www.amtecs.co.uk |