



MOTOR DATA SHEET

MOTOR PART CODE:

0.1883TECAB34

FRAME SIZE:

801-8

	50Hz
Output (kW)	0.18
Rotation Speed (rpm)	680
Voltage	230/400
Full Load Current (A)	1.45 0.84
Full Load Torque (Nm)	2.527941176

	60Hz
Output (kW)	0.216
Rotation Speed (rpm)	816
Voltage	276 480
Full Load Current (A)	1.45 0.84
Full Load Torque (Nm)	2.11

Efficiency Data

100%	75%	50%
51	48.3	41.4

Factory Reference	MS801-8
Tst/Tn (times)	1.5
Tmax/Tn	1.7
Noise (dB)	52
Moment of inertia	0.002097503
Type of feet	Removable feet
Protection	IP55
Rotation Direction	F / R
Cable Glands	1 - M20× 1.5
Paint Colour	RAL 7024
Efficiency	IE1
Bearing (DE)	6204 2RS C3

Power Factor (cos)	0.61
Tmin/Tn	1.3
Ist/In (Times)	2.8
Net Weight (Kg)	9.4
Housing material	Aluminum
Insulation Class	F
Thermal Protection	PTC 130°C
Duty Cycle	S1
Cooling	IC411
Ambient Temperature	-20°C to +40°
Bearing Brand	NSK
Bearing (NDE)	6204 2RS C3

Motors designed and manufactured in accordance with:

IEC 60034
IEC 60038
IEC 60072
2014/30/EU (EMC)
2014/35/EU (LVD)
2011/65/EU (RoHS 2)

www.tecmotors.co.uk

TEC Electric Motors Ltd. reserves the right to amend or change motor designs or data sheet information