



Specification **IEC 60034-1**
 Manufacturer **AmTecs**
 Motor type **AM3-IE3 280M6**
 Rated power **55 kW S1 Duty**
 Speed **985 rpm**
 Voltage **400V / 690V**
 Frequency **50 Hz**
 Connection **Delta / Star**
 Full load current **98.1 A / 56.9 A**
 No-load current
 Enclosure **IP55**
 Insulation class **F (temp. rise B)**
 Max. ambient temp **40 °C**
 Max. altitude **1000 mtr above sea level**
 Comment
 Cable entry **M63 x 1.5**
 Construction **Cast Iron**
 Weight **576 Kg**
 Type number
 Warranty

Efficiency class **IE3**
 Load data **100%**
 Efficiency **94.1 %**
 Power factor **0.86**
 Sound pressure level (1m) **78 dB(A)**
 Resistance R20 (open)
 Resistance R20 (Delta)
 Full load torque **533.2 Nm**
 Starting / Full load torque **2**
 Pull up / Full load torque
 Pull out / Full load torque **2.3**
 Starting / Full load current (DOL) **6**
 Starting / Full load current (Y/D)
 Rotor Inertia
 Bearing DE **6317**
 Bearing NDE **6314**

| | |
|--|--------------------|
| AmTecs Ltd | |
| Charnham Park, Hungerford Berkshire, RG17 0YT | |
| Tel: +44 (0) 1488 686970 | sales@amtecs.co.uk |
| Fax: +44 (0) 1488 686968 | www.amtecs.co.uk |