AM3-IE3 280S8 (B3)

AMTECS



Remarks:

1. Glands: 1 off M63 x 1.5 and 1 off M16 x 1.5, Blanking plug 1 off M63 x 1.5
2. Eye bolt M24
3. 3 off PTC Thermistors 150°C
4. DE and NDE Regreasing points

DRAWN	JamesSouter	15/04/2024
CHECKED	Oliver Young	11/07/2024
QA		
MFG		
APPROVED		

AMTECS LTD

TITLE: AM3-IE3 280S4-10 (B3)

SIZE: A3 | DWG NO: AM3-IE3 280S4-10 (B3) | REV

SCALE: 1:11 | SHEET 1 OF 1

Specification	**IEC 60034-1**	Efficiency class	**IE3**
Manufacturer	**AmTecs**	Load data	100%
Motor type	**AM3-IE3 280S8**	Efficiency	**91.8** %
Rated power	**37** kW **S1** Duty	Power factor	**0.79**
Speed	**740** rpm	Sound pressure level (1m)	**76** dB(A)
Voltage	**400V / 690V**	Resistance R20 (open)	
Frequency	**50** Hz	Resistance R20 (Delta)	
Connection	**Delta / Star**		
Full load current	**73.6 A / 42.7 A**	Full load torque	**477.5** Nm
No-load current		Starting / Full load torque	**2.2**
Enclosure	**IP55**	Pull up / Full load torque	
Insulation class	**F (temp. rise B)**	Pull out / Full load torque	**2.4**
Max. ambient temp	**40** °C		
Max. altitude	**1000** mtr above sea level		
Comment			
Cable entry	**M63 x 1.5**	Starting / Full load current (DOL)	**5.8**
Construction	**Cast Iron**	Starting / Full load current (Y/D)	
Weight	**545** Kg	Rotor Inertia	
Type number		Bearing DE	**6317**
Warranty		Bearing NDE	**6314**

AmTecs Ltd
Charnham Park, Hungerford
Berkshire, RG17 0YT
Tel: +44 (0) 1488 686970
Fax: +44 (0) 1488 686968
sales@amtecs.co.uk
www.amtecs.co.uk

We make all efforts to better our products. Versions, technical data and figures could be changed therefore. They are not binding before written confirmation.