




This drawing serves only as a sketch to show dimensions.
The product delivered may differ. A detailed description of the product can be found below.

AMTECS LTD		
TITLE		
AMA (B34S)		
SIZE	DWG NO	REV
SHEET 1 OF 1		

Specification	IEC 60034-1
Manufacturer	AmTecs
Motor type	AMAB-IE3 112M2
Rated power	4 kW S1 Duty
Speed	2920 rpm
Voltage	400V / 690V
Frequency	50 Hz
Connection	Delta / Star
Full load current	7.45 A / 4.32 A
No-load current	
Enclosure	IP55
Insulation class	F (temp. rise B)
Max. ambient temp	40 °C
Max. altitude	1000 mtr above sea level
Comment	
Cable entry	M25 x 1.5
Construction	Aluminium
Weight	45 Kg
Type number	
Warranty	
Brake Torque	40 (Nm)
Brake Response	0.48 (ms)
Brake Power	75 (W)
Brake Voltage	170

Efficiency class	IE3
Load data	100%
Efficiency	88.1 %
Power factor	0.88
Sound pressure level (1m)	77 dB(A)
Resistance R20 (open)	
Resistance R20 (Delta)	
Full load torque	13.1 Nm
Starting / Full load torque	2.2
Pull up / Full load torque	
Pull out / Full load torque	2.3

Starting / Full load current (DOL)	8.5
Starting / Full load current (Y/D)	
Rotor Inertia	
Bearing DE	6306
Bearing NDE	6306

AmTecs Ltd	
Charnham Park, Hungerford	
Berkshire, RG17 0YT	
Tel: +44 (0) 1488 686970	sales@amtecs.co.uk
Fax: +44 (0) 1488 686968	www.amtecs.co.uk