



MOTOR DATA SHEET

MOTOR PART CODE: **UMDA132M2-2/4CT**

FRAME SIZE: **132**

3~400 V, 50Hz - 2/4 Poles 2870/1440 rpm constant torque

	High Speed - 2 Pole	Low Speed - 4 Pole
Output (kW)	8	6.6
Rotation Speed (rpm)	2870	1440
Voltage	400V 3 Phase	400V 3 Phase
Full Load Current (A)	16.76	13.09
Efficiency (%)	82.0	84.0
Power Factor (cos Ø)	0.84	0.86
Starting Torque Ta/Tn	2.0	2.0
Starting Current Ia/In	6.0	6.0
Maximum Torque Tm/Tn	2.2	2.2
Full Load Torque (Nm)	26.62	43.77

Factory Reference	UMDA 132 M2 2/4
Motor Type	Constant Torque
Pole / Speed	2/4 Pole - 2870/1440rpm
Starting Torque Ta/Tn	2.0 / 2.0
Starting Current Ia/In	6.0 / 6.0
Maximum Torque Tm/Tn	2.2 / 2.2

Frame Size	132
Supply	3~400 V, 50Hz
Output (kW)	8 / 6.6
Full Load Current (A)	16.76 / 13.09
Full Load Torque (Nm)	26.62 / 43.77
Net Weight (Kg)	49.6

Motors designed and manufactured in accordance with:

IEC 60034 | IEC 60038 | IEC 60072 | 2014/30/EU (EMC) | 2014/35/EU (LVD) | 2011/65/EU (RoHS 2)

www.wormgearmotorsonline.com

Worm Gear Motors Online reserves the right to amend or change motor data sheet information.