



# MOTOR DATA SHEET

MOTOR PART CODE: **UMDA80M2-2/4CT**

FRAME SIZE: **80**

**3~400 V, 50Hz - 2/4 Poles 2800/1400 rpm constant torque**

	High Speed - 2 Pole	Low Speed - 4 Pole
Output (kW)	0.75	0.60
Rotation Speed (rpm)	2800	1400
Voltage	400V 3 Phase	400V 3 Phase
Full Load Current (A)	1.88	1.65
Efficiency (%)	67.0	68.0
Power Factor (cos Ø)	0.86	0.77
Starting Torque Ta/Tn	1.8	1.8
Starting Current Ia/In	4.5	4.5
Maximum Torque Tm/Tn	2.0	2.0
Full Load Torque (Nm)	2.56	4.09

Factory Reference	UMDA 80 M2 2/4
Motor Type	Constant Torque
Pole / Speed	2/4 Pole - 2800/1400rpm
Starting Torque Ta/Tn	1.8 / 1.8
Starting Current Ia/In	4.5 / 4.5
Maximum Torque Tm/Tn	2.0 / 2.0

Frame Size	80
Supply	3~400 V, 50Hz
Output (kW)	0.75 / 0.60
Full Load Current (A)	1.88 / 1.65
Full Load Torque (Nm)	2.56 / 4.09
Net Weight (Kg)	10.0

Motors designed and manufactured in accordance with:

IEC 60034 | IEC 60038 | IEC 60072 | 2014/30/EU (EMC) | 2014/35/EU (LVD) | 2011/65/EU (RoHS 2)

[www.wormgearmotorsonline.com](http://www.wormgearmotorsonline.com)

Worm Gear Motors Online reserves the right to amend or change motor data sheet information.